

Floor Care – Strippers

BLITZ

No-rinse, Floor Finish Stripper



- For use on all waxes, finishes, sealers and other metal interlock polymers

PHYSICAL PROPERTIES	PACKAGING
Appearance: Liquid clear	S248628-04 – 4-1 gallons
Specific gravity: 1.052-1.062	S248628-05 – 5 gallon pail
Color: Clear	
pH: >13	
Fragrance: Sassafras	
Dilution: Up to 1:16	

DIRECTIONS: Apply diluted solution to floor with wet mop. Let solution stand 5-10 minutes. Keep floor wet. Remop if necessary. Use scrub brush or automatic scrubber with coarse pad to work stripper into old floor finish. Pick up the solution while still wet. If no residue remains, apply floor finish. If necessary, damp mop the floor with clean water. If floor has a heavy buildup of dirty, old finish, then let solution stand 30 minutes - 1 hour before scrubbing or repeat basic steps until clean. Light stripping: 16 parts water to 1 part BLITZ. Medium stripping: 10 parts water to 1 part BLITZ. Heavy duty stripping: 5 parts water to 1 part BLITZ. CAUTION: Contains alkaline ingredients.

STORAGE and HANDLING: Keep container tightly capped with label intact. Do not reuse containers. Can cause eye irritation. Do not get in eyes. Harmful if swallowed. First Aid: Eye contact-Remove contact lenses. Flood eyes with water for at least 15 minutes holding eyelids apart. Ingestion-If swallowed, drink large amounts of water. Skin Contact-Wear gloves to prevent irritation. If irritation persists, seek medical advice.

Keep Out of Reach of Children. Industrial or Institutional Use Only.



1610 North 170th East Avenue | Tulsa, OK 74116
Phone: 918.439.4329 | 888.834.2001 | Fax: 918.439.4203
summitprochem.com