

USDA – Acid Cleaners

CHEM CARE AC-3

Scale, Rust and Oil Remover



- USDA code A3
- Scale, rust, and oil removal from stainless steel surfaces
- Used for exterior surfaces and CIP systems
- High-foaming

PHYSICAL PROPERTIES	PACKAGING
Appearance: Liquid, color red	S810165-04 – 4-1 gallons
Specific gravity: 1.296-1.304	S810165-05 – 5 gallon pail
Color: Red	S810165-55 – 55 gallon drum
pH: <1.0	
Odor: Bland	
Dilution: Up to 1:128	

DIRECTIONS: GENERAL CLEANING: Depending upon scale and soil build-up, dilute 1-10 ounces of AC-3 per gallon of water. Brush, scrub, soak or spray solution onto equipment. Allow contact for 3-10 minutes. Rinse thoroughly with clean, potable water. Effective for quick removal of milkstone. Harmless to stainless steel and rubber when used as directed. USE IN: Packing plants, dairies, smokehouses, poultry and fish processing plants, fast-food services, bottling plants and breweries.

STORAGE and HANDLING: Keep container tightly capped with label intact. Do not reuse containers. Can cause eye irritation. Do not get in eyes. Harmful if swallowed. First Aid: Eye contact-Remove contact lenses. Flood eyes with water for at least 15 minutes holding eyelids apart. Ingestion-If swallowed, drink large amounts of water. Skin Contact-Wear gloves to prevent irritation. If irritation persists, seek medical advice.

Keep Out of Reach of Children. Industrial or Institutional Use Only.



1610 North 170th East Avenue | Tulsa, OK 74116
Phone: 918.439.4329 | 888.834.2001 | Fax: 918.439.4203
summitprochem.com