

USDA – Acid Cleaners

LF ACID

For Cleaning and Descaling



- USDA code A3
- Scale removal from stainless steel surfaces
- Used for exterior surfaces and CIP systems
- Low-foaming, free-rinsing and non-fuming

PHYSICAL PROPERTIES	PACKAGING
Appearance: Liquid, clear red	S704747-04 – 4-1 gallons
Specific gravity: 1.30-1.36	S704747-05 – 5 gallon pail
Color: Red	S704747-55 – 55 gallon drum
pH: 13.5 @ 23°C	
Odor: Bland	
Dilution: Up to 1:128	

DIRECTIONS: TO CLEAN DAIRY PIPELINES AND TANKS: Depending upon milkstone build-up, dilute 1-2 ounces of LF ACID per 10 gallons of water. Circulate through equipment at 140°F for 5-7 minutes. Rinse thoroughly with clean, potable water. GENERAL CLEANING: Depending upon scale and soil build-up, dilute 1-5 ounces of LF ACID per gallon of water. Brush, scrub, soak or spray solution onto equipment. Allow contact for 3-10 minutes. Rinse thoroughly with clean, potable water. It is a violation of federal law to use this product in a manner inconsistent with its labeling.

STORAGE and HANDLING: Keep container tightly capped with label intact. Do not reuse containers. Can cause eye irritation. Do not get in eyes. Harmful if swallowed. First Aid: Eye contact-Remove contact lenses. Flood eyes with water for at least 15 minutes holding eyelids apart. Ingestion-If swallowed, drink large amounts of water. Skin Contact-Wear gloves to prevent irritation. If irritation persists, seek medical advice.

Keep Out of Reach of Children. Industrial or Institutional Use Only.



1610 North 170th East Avenue | Tulsa, OK 74116
Phone: 918.439.4329 | 888.834.2001 | Fax: 918.439.4203
summitprochem.com