

Industrial and Vehicle SURF'S UP

Truck Wash



- Industrial vehicle wash
- Penetrates heavy soils
- Removes grease and oils

PHYSICAL PROPERTIES	PACKAGING
Appearance: Liquid	SCW0414-04 – 4-1 gallons
Specific gravity: 1.026	SCW0414-05 – 5 gallon pail
Color: Blue/green	SCW0414-55 – 55 gallon drum
pH: 12.8-13.9	
Odor: Bland	
Dilution: Up to 1:4	

DIRECTIONS: Super-concentrate-alkaline compound for degreasing, cleaning and removing tough grime from heavily soiled vehicles, especially for industrial vehicle use. 2 ounces per gallon for light soils, up to one gallon concentrate to four gallons of water for extremely tough grease and dirt.

STORAGE and HANDLING: Keep container tightly capped with label intact. Do not reuse containers. Can cause eye irritation. Do not get in eyes. Harmful if swallowed. First Aid: Eye contact-Remove contact lenses. Flood eyes with water for at least 15 minutes holding eyelids apart. Ingestion-If swallowed, drink large amounts of water. Skin Contact-Wear gloves to prevent irritation. If irritation persists, seek medical advice.

Keep Out of Reach of Children. Industrial or Institutional Use Only.



1610 North 170th East Avenue | Tulsa, OK 74116
Phone: 918.439.4329 | 888.834.2001 | Fax: 918.439.4203
summitprochem.com